

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AaA: Aastad-----	85	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
Ac: Antler-----	50	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.80 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.90 0.91	Fair Depth to saturated zone	0.91
Colvin-----	30	Fair Carbonate content Low content of organic matter Water erosion	0.46 0.50 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.87	Poor Depth to saturated zone Carbonate content	0.00 0.46
At: Antler-----	45	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.80 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.90 0.91	Fair Depth to saturated zone	0.91
Tonka-----	25	Poor Too clayey Water erosion	0.00 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.56	Poor Depth to saturated zone Too Clayey	0.00 0.00
AvA: Antler-----	45	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.80 0.99	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.90 0.91	Fair Depth to saturated zone	0.91

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Hamerly-----	40	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.80 0.99	Fair Low strength Shrink-swell Depth to saturated zone	0.22 0.87 0.91	Fair Carbonate content Depth to saturated zone	0.80 0.91
BbE: Barnes-----	50	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.92 0.99	Fair Low strength Shrink-swell Slope	0.78 0.87 0.92	Poor Slope	0.00
Buse-----	25	Poor Stone content Low content of organic matter Carbonate content	0.00 0.12 0.80	Poor Slope Stone content Low strength Shrink-swell Cobble content	0.00 0.00 0.78 0.87 0.92	Poor Slope Hard to reclaim Rock fragments Salinity	0.00 0.50 0.50 0.88
Be: Bearden-----	85	Fair Carbonate content Water erosion	0.68 0.90	Poor Low strength Shrink-swell Depth to saturated zone	0.00 0.87 0.91	Fair Depth to saturated zone	0.91
Bo: Borup-----	85	Fair Low content of organic matter Too sandy Carbonate content	0.12 0.18 0.46	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Too sandy Carbonate content	0.00 0.18 0.92
BpF: Buse-----	50	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Poor Slope Low strength Shrink-swell	0.00 0.22 0.87	Poor Slope	0.00

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Forman-----	20	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Poor Slope Low strength Shrink-swell	0.00 0.22 0.87	Poor Slope Carbonate content	0.00 0.97
Co: Colvin-----	90	Fair Carbonate content Low content of organic matter Water erosion	0.46 0.50 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.87	Poor Depth to saturated zone Carbonate content	0.00 0.46
DcA: Dickey-----	80	Fair Low content of organic matter Water erosion	0.12 0.99	Fair Low strength Shrink-swell	0.78 0.99	Good	
DcB: Dickey-----	80	Fair Low content of organic matter Water erosion	0.12 0.99	Fair Low strength Shrink-swell	0.78 0.99	Good	
Dm: Divide-----	55	Fair Carbonate content Low content of organic matter	0.46 0.50	Fair Depth to saturated zone	0.91	Poor Rock fragments Hard to reclaim Depth to saturated zone	0.00 0.18 0.91
Marysland-----	40	Fair Low content of organic matter Carbonate content	0.12 0.68	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Carbonate content Hard to reclaim	0.00 0.68 0.92

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Do: Doran-----	80	Fair Low content of organic matter Water erosion	0.12 0.99	Poor Low strength Shrink-swell	0.00 0.12	Good	
Dv: Castlewood-----	85	Poor Too clayey	0.00	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.12	Poor Too Clayey Depth to saturated zone	0.00 0.00
EcA: Eckman-----	85	Fair Water erosion	0.90	Good		Good	
EcB: Eckman-----	80	Fair Water erosion	0.90	Good		Good	
EeC: Eckman-----	65	Fair Water erosion	0.90	Good		Good	
Zell-----	25	Fair Low content of organic matter Water erosion Carbonate content	0.12 0.90 0.97	Good		Fair Carbonate content	0.97
Eh: Embden-----	70	Fair Low content of organic matter	0.50	Good		Good	
Hamar-----	20	Fair Low content of organic matter Too sandy Droughty	0.12 0.23 0.97	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Too sandy	0.00 0.23

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
FdA: Fordville-----	90	Fair Low content of organic matter Too sandy	0.12 0.14	Good		Poor Rock fragments Too sandy Hard to reclaim	0.00 0.14 0.18
FeB: Fordville-----	70	Fair Low content of organic matter Too sandy	0.12 0.14	Good		Poor Rock fragments Too sandy Hard to reclaim	0.00 0.14 0.18
Renshaw-----	25	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Good		Poor Rock fragments Hard to reclaim Too sandy	0.00 0.08 0.14
FoA: Forman-----	70	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Carbonate content	0.97
Aastad-----	20	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
FoB: Forman-----	60	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Carbonate content	0.97

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Aastad-----	25	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
FOC: Forman-----	60	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Carbonate content	0.97
Aastad-----	25	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
FoD: Forman-----	55	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Slope Carbonate content	0.37 0.97
Aastad-----	25	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
FsB: Forman-----	65	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Carbonate content	0.97

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Aastad-----	25	Fair Low content of organic matter Too clayey Carbonate content Water erosion	0.12 0.95 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.95
FuC: Forman-----	55	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Carbonate content	0.97
Buse-----	25	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Fair Low strength Shrink-swell	0.22 0.87	Good	
FuD: Forman-----	55	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Slope Carbonate content	0.37 0.97
Buse-----	25	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Fair Low strength Shrink-swell	0.22 0.87	Fair Slope	0.37
FuE: Forman-----	45	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Slope Shrink-swell	0.22 0.50 0.87	Poor Slope Carbonate content	0.00 0.97

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Buse-----	25	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Fair Low strength Slope Shrink-swell	0.22 0.50 0.87	Poor Slope	0.00
FvE: Forman-----	55	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.97 0.99	Fair Low strength Slope Shrink-swell	0.22 0.50 0.87	Poor Slope Carbonate content	0.00 0.97
Buse-----	20	Poor Stone content Low content of organic matter Carbonate content	0.00 0.12 0.80	Poor Slope Stone content Low strength Shrink-swell Cobble content	0.00 0.00 0.78 0.87 0.92	Poor Slope Hard to reclaim Rock fragments Salinity	0.00 0.50 0.50 0.88
Ga: Gardena-----	85	Fair Water erosion	0.90	Good		Good	
Gp: Orthents, Gravelly--	100	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.29	Poor Slope	0.00	Poor Rock fragments Slope Too sandy Hard to reclaim	0.00 0.00 0.14 0.18
GyA: Glyndon-----	85	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.32 0.90	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone Carbonate content	0.53 0.68

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Ha: Hamar-----	90	Fair Low content of organic matter Too sandy Droughty	0.12 0.23 0.97	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Too sandy	0.00 0.23
HbA: Hamerly-----	45	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.80 0.99	Fair Low strength Shrink-swell Depth to saturated zone	0.22 0.87 0.91	Fair Carbonate content Depth to saturated zone	0.80 0.91
Tonka-----	25	Poor Too clayey Water erosion	0.00 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.56	Poor Depth to saturated zone Too Clayey	0.00 0.00
HcA: Hamerly-----	65	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.80 0.99	Fair Low strength Shrink-swell Depth to saturated zone	0.22 0.87 0.91	Fair Carbonate content Depth to saturated zone	0.80 0.91
Vallars-----	20	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Poor Depth to saturated zone Low strength	0.00 0.22	Poor Depth to saturated zone Carbonate content	0.00 0.46

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
HcB: Hamerly-----	65	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.80 0.99	Fair Low strength Shrink-swell Depth to saturated zone	0.22 0.87 0.91	Fair Carbonate content Depth to saturated zone	0.80 0.91
Vallars-----	20	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Poor Depth to saturated zone Low strength	0.00 0.22	Poor Depth to saturated zone Carbonate content	0.00 0.46
HdD: Hattie-----	90	Poor Too clayey Carbonate content	0.00 0.97	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey Slope Carbonate content	0.00 0.37 0.97
HdE: Hattie-----	85	Poor Too clayey Carbonate content	0.00 0.97	Poor Low strength Slope Shrink-swell	0.00 0.00 0.12	Poor Slope Too Clayey Carbonate content	0.00 0.00 0.97
HkD: Hattie-----	45	Poor Too clayey Carbonate content	0.00 0.97	Poor Low strength Shrink-swell Slope	0.00 0.12 0.92	Poor Too Clayey Slope Carbonate content	0.00 0.00 0.97
Kloten-----	40	Poor Droughty Depth to bedrock	0.00 0.00	Poor Depth to bedrock Low strength Shrink-swell Slope	0.00 0.22 0.87 0.92	Poor Depth to bedrock Slope	0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
HmA: Hecla-----	60	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.50 0.90	Good		Poor Too sandy	0.00
Hamar-----	30	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.23 0.97	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Too sandy	0.00 0.23
HsB: Heimdal-----	55	Fair Low content of organic matter Carbonate content	0.12 0.68	Good		Fair Carbonate content	0.92
Sisseton-----	20	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.68 0.99	Good		Fair Carbonate content	0.95
HsC: Heimdal-----	50	Fair Low content of organic matter Carbonate content	0.12 0.68	Good		Fair Carbonate content	0.92
Sisseton-----	25	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.68 0.99	Good		Fair Carbonate content	0.95

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
HvA: Heimdal-----	75	Fair Low content of organic matter Carbonate content	0.12 0.68	Good		Fair Carbonate content	0.92
Svea-----	15	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.90	Fair Carbonate content Sodium content	0.97 0.98
HvB: Heimdal-----	65	Fair Low content of organic matter Carbonate content	0.12 0.68	Good		Fair Carbonate content	0.92
Svea-----	25	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.90	Fair Carbonate content Sodium content	0.97 0.98
La: Ladelle-----	90	Good		Poor Low strength Shrink-swell	0.00 0.93	Good	
Lm: Lamoure-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Depth to saturated zone Shrink-swell	0.00 0.00 0.99	Poor Depth to saturated zone	0.00
Lp: La Prairie-----	90	Fair Carbonate content	0.92	Poor Low strength Shrink-swell	0.00 0.87	Fair Carbonate content	0.92

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Lt: Lamoure-----	85	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.99	Poor Depth to saturated zone	0.00
Lu: Ludden-----	90	Poor Too clayey	0.00	Poor Low strength Shrink-swell	0.00 0.12	Poor Too Clayey	0.00
M-W: Miscellaneous Water-	100	Not rated		Not rated		Not rated	
MaB: Maddock-----	90	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.88 0.97	Good		Poor Too sandy	0.00
MaD: Maddock-----	85	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.88 0.97	Fair Slope	0.98	Poor Too sandy Slope	0.00 0.00
Mr: Southam-----	90	Poor Too clayey Carbonate content Water erosion	0.00 0.92 0.99	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.20	Poor Depth to saturated zone Too Clayey Salinity	0.00 0.00 0.88

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Mw: Marysland-----	85	Fair Low content of organic matter Carbonate content	0.12 0.68	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Carbonate content Hard to reclaim	0.00 0.68 0.92
Or: Orthents, Loamy-----	100	Fair Too clayey	0.98	Poor Low strength Shrink-swell	0.00 0.87	Fair Too Clayey	0.93
Pa: Parnell-----	85	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.22	Poor Depth to saturated zone Too Clayey	0.00 0.00
PeA: Peever-----	85	Fair Too clayey Low content of organic matter Water erosion	0.12 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Fair Too Clayey Sodium content	0.08 0.98
PeB: Peever-----	85	Fair Too clayey Low content of organic matter Water erosion	0.12 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Fair Too Clayey Sodium content	0.08 0.98
PeC: Peever-----	80	Fair Too clayey Low content of organic matter Water erosion	0.12 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Fair Too Clayey Sodium content	0.08 0.98

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
PhA: Peever-----	70	Fair Too clayey Low content of organic matter Water erosion	0.12 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Fair Too Clayey Sodium content	0.08 0.98
Cavour-----	25	Poor Too clayey Low content of organic matter Salinity Sodium content Carbonate content Water erosion	0.00 0.12 0.50 0.90 0.99 0.99	Poor Low strength Shrink-swell	0.00 0.55	Poor Too Clayey Salinity Sodium content	0.00 0.00 0.90
Pk: Peever-----	60	Fair Too clayey Low content of organic matter Water erosion	0.12 0.50 0.99	Poor Low strength Shrink-swell	0.00 0.12	Fair Too Clayey Sodium content	0.08 0.98
Tonka-----	30	Poor Too clayey Water erosion	0.00 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.56	Poor Depth to saturated zone Too Clayey	0.00 0.00
Pm: Playmoor-----	85	Fair Low content of organic matter Salinity Sodium content	0.12 0.88 0.97	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.87	Poor Depth to saturated zone Salinity	0.00 0.00
PoA: Poinsett-----	90	Fair Low content of organic matter Water erosion Carbonate content	0.88 0.90 0.92	Poor Low strength Shrink-swell	0.00 0.87	Fair Carbonate content	0.92

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
PoB: Poinsett-----	90	Fair Low content of organic matter Water erosion Carbonate content	0.88 0.90 0.92	Poor Low strength Shrink-swell	0.00 0.87	Fair Carbonate content	0.92
Ra: Rauville-----	90	Good		Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.99	Poor Depth to saturated zone	0.00
ReA: Renshaw-----	85	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Good		Poor Rock fragments Hard to reclaim Too sandy	0.00 0.08 0.14
ReB: Renshaw-----	85	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Good		Poor Rock fragments Hard to reclaim Too sandy	0.00 0.08 0.14
RhB: Renshaw-----	70	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Good		Poor Rock fragments Hard to reclaim Too sandy	0.00 0.08 0.14
Sioux-----	20	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.16	Good		Poor Too sandy Rock fragments Hard to reclaim	0.00 0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
RhD: Renshaw-----	50	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Good		Poor Rock fragments Slope Hard to reclaim Too sandy	0.00 0.00 0.08 0.14
Sioux-----	40	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.16	Good		Poor Too sandy Rock fragments Hard to reclaim Slope	0.00 0.00 0.00 0.00
RsE: Renshaw-----	50	Fair Low content of organic matter Too sandy Droughty	0.12 0.14 0.66	Fair Slope	0.92	Poor Rock fragments Slope Hard to reclaim Too sandy	0.00 0.00 0.08 0.14
Sioux-----	35	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.16	Poor Slope	0.00	Poor Too sandy Rock fragments Hard to reclaim Slope	0.00 0.00 0.00 0.00
RtA: Rentill-----	85	Poor Too clayey Low content of organic matter Carbonate content Water erosion	0.00 0.12 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.45	Poor Too Clayey Carbonate content	0.00 0.92

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
RtB: Rentill-----	85	Poor Too clayey Low content of organic matter Carbonate content Water erosion	0.00 0.12 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.45	Poor Too Clayey Carbonate content	0.00 0.92
Sb: Minnewaukan-----	90	Poor Wind erosion Too sandy Low content of organic matter Droughty	0.00 0.16 0.50 0.69	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone Too sandy Rock fragments	0.00 0.16 0.88
ScF: Sieche-----	80	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.99	Poor Slope Low strength Shrink-swell	0.00 0.00 0.56	Poor Slope Too Clayey	0.00 0.00
SnA: Sinai-----	90	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Low strength Shrink-swell	0.00 0.00	Poor Too Clayey	0.00
SnB: Sinai-----	90	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Low strength Shrink-swell	0.00 0.00	Poor Too Clayey	0.00
SsF: Sisseton-----	70	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.68 0.99	Poor Slope	0.00	Poor Slope Carbonate content	0.00 0.95

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
StD: Sisseton-----	45	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.68 0.99	Fair Slope	0.92	Poor Slope Carbonate content	0.00 0.95
Heimdal-----	30	Fair Low content of organic matter Carbonate content	0.12 0.68	Fair Slope	0.92	Poor Slope Carbonate content	0.00 0.92
SvC: Svea-----	90	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.97 0.99	Poor Low strength Shrink-swell	0.00 0.90	Fair Carbonate content Sodium content	0.97 0.98
SwA: Sverdrup-----	85	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.46	Good		Poor Too sandy	0.00
SwB: Sverdrup-----	85	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.46	Good		Poor Too sandy	0.00
Tk: Tonka-----	85	Poor Too clayey Water erosion	0.00 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.56	Poor Depth to saturated zone Too Clayey	0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
To: Towner-----	85	Poor Too sandy Low content of organic matter Water erosion Carbonate content	0.00 0.12 0.90 0.92	Fair Low strength Shrink-swell	0.78 0.98	Poor Too sandy	0.00
Un: Ulen-----	90	Fair Carbonate content Droughty Low content of organic matter	0.80 0.85 0.88	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone Carbonate content	0.53 0.80
VhA: Vallars-----	60	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.46 0.99	Poor Depth to saturated zone Low strength	0.00 0.22	Poor Depth to saturated zone Carbonate content	0.00 0.46
Hamerly-----	30	Fair Low content of organic matter Carbonate content Water erosion	0.12 0.80 0.99	Fair Low strength Shrink-swell Depth to saturated zone	0.22 0.87 0.91	Fair Carbonate content Depth to saturated zone	0.80 0.91
Parnell-----	5	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.90	Poor Depth to saturated zone Low strength Shrink-swell	0.00 0.00 0.22	Poor Depth to saturated zone Too Clayey	0.00 0.00
VnA: Vienna-----	85	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.89	Fair Carbonate content	0.99

Section II
Soil and Site Information

Construction Materials Table 2
Roberts County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
VnB: Vienna-----	80	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.89	Fair Carbonate content	0.99
VnC: Vienna-----	80	Fair Low content of organic matter Carbonate content Water erosion	0.50 0.92 0.99	Poor Low strength Shrink-swell	0.00 0.89	Fair Carbonate content	0.99
W: Water-----	100	Not rated		Not rated		Not rated	
Wa: Waubay-----	90	Fair Water erosion Carbonate content	0.90 0.97	Poor Low strength Shrink-swell	0.00 0.87	Fair Carbonate content	0.97
ZeD: Zell-----	60	Fair Low content of organic matter Water erosion Carbonate content	0.12 0.90 0.97	Fair Slope	0.92	Poor Slope Carbonate content	0.00 0.97
Eckman-----	25	Fair Water erosion	0.90	Good		Fair Slope	0.37

